

Last Updated: 20/05/2024

Product Name: GP cement

Product Description:

GP cement is suitable for a wide array of application from household repair to professional applications in Mortars, Concrete, Renders, Grouting & Repair in construction projects. GP cement is grey in Colour. Surelevel GP cement complies with the standards of AS 3972 and EN-197-1 as 52.5 N cement.




Physical Properties:

| Property | | Standard AS3972 |
|-----------------------------|---------------|-----------------|
| Compressive strength 7 Day | >35 MPa | 35 MPa Min |
| Compressive strength 28 Day | >52.5 MPa | 45 MPa Min |
| Initial Setting Time | >1Hour | 45 Minutes Min |
| Final Setting Time | 2.5-5 Hours | 6 Hours Max |
| Soundness | Less than 4mm | 5mm Max |

Health & Safety:

This product is classified as hazardous according to criteria of Work Safe Australia. Material containing Portland Cement and sand now fall into this category. Continuous or extended contact with this product may cause irritation as well as respiratory issues such as bronchitis or silicosis.

- ✔ During use avoid inhalation of dust, contact with skin and eyes.
- ✔ Suitable protective clothing, dust masks, gloves and eye protection should be worn.
- ✔ Continual or extended contact with cement products can cause skin irritation.
- ✔ If skin irritation occurs, remove contaminated clothing and flush skin thoroughly with water for a minimum of 15 minutes. Contact Poisons Information Centre or consult medical adviser.



SURE LEVEL
International



www.surelevel.com.au

✓ Safety Data Sheets (SDS) are available on request from the office. Read the SDS and product data sheet carefully before using any product.

Document Date: February, 2024 (REV 4.5)

Contact Details

Entity name: SURE LEVEL INTERNATIONAL PTY LTD

Location: 12 Northgate Dr, Thomastown VIC 3074

Phone: + 61 3 9464 5189

Email: info@surelevel.com.au

website: www.surelevel.com.au



+61 3 9464 5189



Info@surelevel.com.au



12 Northgate Dr, Thomastown VIC 3074