

## Product Name: SURE PRIMER DILUTED

### Product Description:

Sure Level International Sure Primer Diluted is a multi-purpose primer for walls and floors. It protects thin-bed mortars and levelling compounds from rapid absorption of water, increases open time, improves adhesion, flexibility and waterproofing, prevents formation of shrinkage cracks. Sure Primer creates a smooth and stable base, improving the performance and longevity of the sealant applied. Features

### Features:

- ✔ Solvent-free, no damage to environment and worker by solvent vapours.
- ✔ No danger of fire or explosion.
- ✔ Improves the strength and solidity of substrates and increases adhesion of tiles, plasters and the sealant applied.
- ✔ Cement based mortars have a good bond to Sure Primer.
- ✔ Protects thin-bed mortars and levelling compounds from too rapid dehydration of water, increases the open time, improves adhesion and prevents formation of shrinkage cracks.

### Benefits:

- ✔ For indoor and outdoor use
- ✔ For walls and floors
- ✔ Priming prior to the application of self levelling compounds
- ✔ Moisture barrier and primer for plaster, gypsum fibre boards, MGO, plaster boards, concrete, asphalt, render, sand, cement screed, anhydrite screed and brickwork before tiling
- ✔ For aerated concrete, sand-lime brick, brickwork and concrete on walls prior to the application of gypsum based plaster
- ✔ To strengthen weak, absorbent screed surfaces and plasters indoors prior to the installation of tiles and mosaics

### Surface Preparation:

- ✔ The substrate must be solid, clean and able to take loads.
- ✔ Remove any spacer lugs, any excess adhesive and any loose or foreign material from the grout joints.
- ✔ Oil stains, bond-reducing residues such as solvent-free adhesive residues, and contaminations have to be thoroughly removed.
- ✔ Freshly applied cement screeds must not have a moisture content above 4%, ground anhydrite and/or gypsum based screeds not more than 0.5%.

### Limitations:

Sure Flex 3000 HD should not be used where or for: -

- ✔ Swimming pools without prior consultation with Sure Level.
- ✔ The substrate is subject to movement.
- ✔ Where the substrate can be affected by strong vibration.
- ✔ On plaster or metals that will rust or oxidise or timber, where natural oils interfere with adhesion.



## Mixing:

- ✔ Product is packaged ready to use.
- ✔ Stir Sure Primer to a uniform consistency. Avoid creating air bubbles or foam.
- ✔ Stir occasionally as needed to keep uniformly mixed.

## Application:

- ✔ Stir Sure Primer thoroughly.
- ✔ Apply a sufficient quantity of Sure Primer with a brush or roller to achieve a uniform coat
- ✔ In case of very absorbent substrates it is recommended to apply a second coat of Sure Primer. Do not apply second coat until the first one has completely cured
- ✔ After curing (scratchproof) apply tile adhesive, plaster or the screed levelers.
- ✔ Do not apply tile adhesive, plaster or the screed levellers until Sure Primer has completely cured.

## Coverage:

- ✔ Depending on the condition of the substrate and the method of application, approximate coverage are:
- ✔ 1L covers 8-12 square meters (one coat)

## Precautions:

- ✔ Do not apply Sure Primer in temperature above 40°C or below 5°C.
- ✔ In case of partial tiling the whole wall area should be primed (e.g. behind the bath or above the tile covering).
- ✔ Do not be diluted with water.
- ✔ Avoid formation of puddles in case of applying Sure Primer on floor areas. Adhesive residues of old coverings have to be completely removed before laying natural stones.
- ✔ Clean tools immediately after use. Once the product has cured it can only be removed by mechanical means.
- ✔ Do not apply Sure Primer in underwater situations.

## Storage:

- ✔ Tightly reseal the package after use.
- ✔ Keep out of reach of children.
- ✔ Protect from freezing.

## Shelf Life:

- ✔ Shelf life is at least 12 months when stored in right condition.

## Packaging:

- ✔ 20Kg/Pail

Technical Information		
Technical Data		
1	Components	One-component
2	Density	Approx. 1.05g/cm <sup>2</sup>
3	Colour	Blue
4	Identification according to - Regulation for hazardous goods/rod - Regulation for hazardous materials	Non hazardous Not subject to identification
5	Shelf life	Approx. 12 months
6	Storage	Cool and dry, but not below -10°C, frozen Sure Primer Diluted is to be slowly thawed and stirred thoroughly
7	Packaging	20kg/pail
8	Coverage	1kg/8-12sqm, one coat

**For further information consult our Technical Department**

## Contact Details

**Entity name:** SURE LEVEL INTERNATIONAL PTY LTD

**Location:** 12 Northgate Dr, Thomastown VIC 3074

**Phone:** + 61 3 9464 5753

**Email:** [info@surelevel.com.au](mailto:info@surelevel.com.au)

**website:** [www.surelevel.com.au](http://www.surelevel.com.au)