







Safety Data Sheet

Product Name: Sure Primer Undiluted

Section 1: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION:					
1.1	Product Name:	Sure Primer Undiluted			
1.2	Supplier Information	Sure Level Australia Pty Ltd 12 Northgate Drive, Thomastown Vic 3074. Phone: + 61 3 9464 5753 Fax: + 61 3 9464 3630 Email: info@surelevel.com.au Web: www.surelevel.com.au			
1.3	Emergency Contact	13 11 26 (Poisons Information Centre)			

Section 2: COMPOSITION, INFORMATION ON INGREDIENTS

·						
CAS#			Chemical Name	Percent		
25067-01-0		Acrylic Latex		45%-75%		
N/A		Defoaming Agent		1%-5%		
N/A			Antioxidant	1%-5%		
N/A		O	ther ingredients determined as non-hazardous	To 100%		
Section 3: HAZARDS IDENTIFICATION						
3.1	Product Name:		Sure Primer Undiluted			
3.2	3.2 Eye:		Fall into eyes possibly causes tears			
3.3	3.3 Skin:		May irritate dry skin.			
3.4 Ingestion:			Small amounts ingested incidental to normal handling will have little or no effect.			
3.5	3.5 Inhalation:		Will cause coughing and a dry throat.			
3.6	chronic:		No.			

Info@surelevel.com.au



Section 4: FIRST AID MEASURESL:					
4.1	Eyes:	Rinse immediately and repeatedly with water			
4.2	Skin:	Wash exposed areas promptly with water			
4.3	Ingestion:	Do not induce vomiting and get prompt medical attention			
4.4	Inhalation:	Wash with plenty of water			
4.5	Notes to Physician:	Wash with plenty of water			
Section 5: FIRE FIGHTING MEASURES					
5.1	Product is non-combustible. No explosive effect expected				
Section 6: ACCIDENTAL RELEASE MEASURES					
6.1	Spills/Leaks:	Prevent product entering drains or waterways. Wear dust mask or respirator. Without creating dust clouds sweep or shovel up and place in plastic drums or pails, fit lids label and place in a safe area to await disposal or recovery. Thoroughly ventilate area before continuing normal work.			
		Section 7: HANDLING AND STORAGE			
7.1	Handling:	Wear suitable protective clothing. Avoid inhaling dusts.			
7.2	Storage:	Store in a cool, dry and well-ventilated area. Avoid generating or accumulating dusts during handling			
Section 8: EXPOSURE CONTROLS, PERSONAL PROTECTION					
8.1	Engineering Controls:	In outdoor use natural ventilation is usually adequate. If extremely dusty conditions prevail or if working in poorly ventilated enclosed areas provide adequate ventilation/dust extraction and exhausts to ensure that the work area is kept below the TWA set.			
8.2	ventilation/dust extraction and exhausts:	Use good quality dust mask in normal use or respirator with particulate filters to AS 1715 & 1716 in very dusty circumstances.			

